

Customer No. 24498  
Attorney Docket No. PF020112  
Office Action Date: 12/04/2009

RECEIVED  
CENTRAL FAX CENTER

APR 01 2010

Amendments to the Claims

This listing of claims will replace all prior versions and listings of claims in the application:

1. (Currently amended) A method for parent election among bridge portals in a transparent wireless bridge, said transparent wireless bridge comprising at least two bridge portals, said method comprising:

determining for each bridge portal the number of wireless ports adapted to directly connect other wireless devices;

electing a parent portal based on the bridge portal with the greatest number of such wireless ports as parent portal, and

directly connecting each other bridge portals to a wireless port of the elected parent portal.

2. (Previously presented) The method according to claim 1, wherein the sum of the number of ports on the wireless interface of a bridge portal, called virtual ports hereafter, and of the number of physical ports of a bridge portal on the wired bus interface is limited to a predefined number, and wherein the respective number of virtual ports and physical ports is configurable.

3. (Previously presented) The method according to claim 1, the elected portal is the only portal that may or may not be root on a local bus connected to that elected portal.

4. (Previously presented) The method according to claim 1, further comprising triggering the election of the parent bridge portal following the association of a new bridge portal.

5. (Previously presented) The method according to claim 4, further comprising, prior to triggering the election, verifying whether the current parent portal has a free virtual port, and in the affirmative, connecting the new portal to that port without triggering the election.

Customer No. 24498  
Attorney Docket No. PF020112  
Office Action Date: 12/04/2009

6. (Previously presented) The method according to claim 1, further comprising rejecting the connection of a new portal if the connection of the new portal would result in an invalid topology.

7. (Previously presented) The method according to claim 1, further comprising storing, at the level of a portal device, at least one of the following:

- the failure cause of a connection of the portal to the parent portal,
- the failure of association of the portal a central controller of the wireless bridge, and

the failure cause of becoming the parent portal.

8. (Cancelled)

9. (Currently amended) A bridge portal device for connection to a wireless bridge comprising a first interface to a wired bus and a second interface to the wireless bridge, comprising microprocessor means for managing ports on its wireless interface for connection to wireless devices according to topology rules defined for the wired bus, said microprocessor means being adapted to participate in a parent portal election process among bridge portals which is a function of the based on the greatest number of wireless ports on the wireless interfaces of portal devices of the wireless bridge.